

MOTION F5m TABLET PC



MIL-STD
810G

IP54

CID2[†]
Certified



PRODUCT SPECIFICATIONS

- PROCESSOR / CACHE**
- Intel® Core™ i7 vPro™ Processor
2.6 GHz 5600U with Turbo Boost to 3.2 GHz
(4MB of L3 cache, 2 Cores/4 Threads)
or
 - Intel® Core™ i5 Processor
2.2 GHz 5200U with Turbo Boost to 2.7 GHz
(3MB of L3 cache, 2 Cores/4 Threads)
or
 - Intel® Core™ i3 Processor
2.0 GHz 5005U
(3MB of L3 cache, 2 Cores/4 Threads)
- OPERATING SYSTEM**
- Windows® 8.1 Pro
 - Windows® 7 Professional 64-bit
- DURABILITY**
- Meets MIL-STD-810G
 - IP54 rated
 - Water, dust and splash resistant
 - Class I Division 2 certified (optional configuration)[†]
 - Durable Gorilla® Glass
 - Rubberized for shock dampening
 - Magnesium-alloy internal frame
 - Molded handle helps prevent drops
- DISPLAY**
- 10.4" XGA (1024 x 768) View Anywhere® Display with Projective Capacitive 10-point Touch TFT AFFS+ LED Backlight with Durable Gorilla® Glass
or
 - 10.4" XGA (1024 x 768) Standard Display with Projective Capacitive 10-point Touch TFT AFFS+ LED Backlight with Durable Gorilla® Glass
 - Intel Display Power Saving Technology (DPST)
- GRAPHICS**
- Intel® HD Graphics 5500 GT2
 - Rotation: 0°, 90°, 270°
- AUDIO CONTROLLER**
- High Definition Audio

- SYSTEM MEMORY**
- DDR3L 1600MHz SDRAM memory
 - Base configuration of 4GB
 - Optional configuration of 8GB or 16GB
- SYSTEM STORAGE**
- m.2 Solid State Drive (SSD) with capacities of 64GB, 128GB or 256GB
 - m.2 Self-encrypting drives (SED) with capacity of 256 GB (optional)*
 - AHCI
- INTEGRATED COMMUNICATIONS**
- Intel® Dual Band Wireless-AC 7265 Wi-Fi and Bluetooth® 4.0
 - Optional Integrated Mobile Broadband - Qualcomm® Gobi™ technology 4G XLTE** Mobile Broadband with either
 - GNSS (GPS + GLONASS)
 - Optional U-Blox 7 GPS
- AUDIO**
- Noise cancellation technology
 - Multi-directional array microphone design with 2 microphones
 - Integrated speaker
- I/O PORTS**
- Docking connector
 - USB 3.0 port with rubberized cover
- EMBEDDED I/O**
- 8.0 Megapixel camera (rear-facing)
 - 2.0 Megapixel front-facing web camera
 - Optional 1D/2D Barcode Reader
- SECURITY**
- Integrated Fingerprint Reader with OmniPass software
 - TCG Trusted Platform Module (TPM) 1.2
 - WinMagic® SecureDoc™ (single-user license)
 - Smart card reader (optional)
 - ISO 7816 PC/SC
 - EMV2 2000 Level 1
 - Computrace® Complete (optional)
- DIMENSIONS**
- 10.0" x 10.0" x .95" (256mm x 256mm x 24.3mm)
- WEIGHT**
- 3.3 lbs.¹ (1.50 kg)
- BATTERY**
- Battery life over 8 hours²
 - Hot swappable Lithium Ion standard battery with 40WHr capacity
- BATTERY CHARGING TIME**
- Standard Battery - 1.5 hours (Tablet PC on/off)³

ACADAPTER	<ul style="list-style-type: none"> • 65W universal, 3-pin jack • 100-240V 1.5A, 50-60Hz 	WARRANTY	<ul style="list-style-type: none"> • 3-year standard warranty
SOFTWARE	<p>Windows® 7 Software</p> <ul style="list-style-type: none"> • SnapWorks® by Motion Camera App • Barcode Reader • Motion/Softex OmniPass™ Security Software • Motion Dashboard Control Panel • Mobile Broadband Connection Manager • Pen and Touch Enabled BIOS Setup • Infineon Security Platform Tools (Optional) <p>Windows® 8 Software</p> <ul style="list-style-type: none"> • SnapWorks® by Motion • Barcode Reader • Motion/Softex OmniPass™ Security Software • Motion Tablet Center • Know Your Motion Tablet • Pen and Touch Enabled BIOS Setup • Infineon Security Platform Tools (Optional) 	STANDARDS	<ul style="list-style-type: none"> • ACPI 3.0b compliant
SYSTEM STATUS LED	<ul style="list-style-type: none"> • Power on/off/stand by LED ring around power button • Battery status LED on back • Battery charge gauge on front 	SAFETY	<ul style="list-style-type: none"> • AS/NZS 60950-1 • Class I Division 2 certified (optional configuration) • FCC/ANSI C63.41 • IC RSS 102 • ETSI EN 62311 • UL, CUL, CE (IEC/EN60950-1 A11/2004) • EU Directive LVD (2006/95/EC) • EU Directive Batteries (2006/66/EC and its amendments) • California Proposition 65 • Technical Instructions for Safe Transport of Dangerous Goods by Air (ICAO Doc #9284) • Emergency Response Guidance for Aircraft incidents involving Dangerous Goods (ICAO Doc #9481)
CONTROL BUTTONS	<ul style="list-style-type: none"> • One 5-way directional for navigation • One function, one Dashboard and two programmable • Secure Attention Sequence (SAS) • Volume controls • Windows Home button • Barcode scan trigger (programmed) 	REGULATORY	<ul style="list-style-type: none"> • AS/NZS 3548:1995 Class B • AS/NZS 4268 • AS/ACIF S042.1 (WCDMA/HSDPA) • AS/ACIF S042.3 (WCDMA/HSDPA) • AS/ACIF S042.1 (GSM/EDGE) • AS/ACIF S042.3 (GSM/EDGE) • CAN/CSA ICES-003 Class B • CAN/CSA RSS-210 Issue 5 • CAN/CSA RSS-310 Issue 2 • CAN/CSA RSS-132 (1xRTT/EVDO-0/EVDO-A) • CAN/CSA RSS-133 (1xRTT/EVDO-0/EVDO-A) • CENELEC EN 60601-1-2 • CENELEC EN 55022 Class B (CISPR22) • CENELEC EN 55024 (CISPR24) • CENELEC EN 61000-3-2 • CENELEC EN 61000-3-3 • ETSI EN 301-893 • ETSI EN 300-328 • ETSI EN 300-440 • ETSI EN 301-489-1 • ETSI EN 301-489-7 • ETSI EN 301-489-17 • ETSI EN 301-489-24 • ETSI EN 301-511 • ETSI EN 301-908 • FCC Part 15 Subpart B Class B • FCC Part 15 Subpart C (2.4 GHz) • FCC Part 15 Subpart E (5 GHz) • FCC Part 22 H (1xRTT/EVDO-0/EVDO-A) • FCC Part 24 E (1xRTT/EVDO-0/EVDO-A) • FCC Part 27 (WCS) • R&TTE (89/336/EEC) & R&TTE (99/5/EC)
BUILT-IN CAMERAS	<p>Rear-Facing Camera</p> <ul style="list-style-type: none"> • Autofocus • 8.0 megapixel resolution • Illuminator light <p>Front-Facing Camera</p> <ul style="list-style-type: none"> • Autofocus • 2.0 megapixel resolution 		
ENVIRONMENTAL	<ul style="list-style-type: none"> • MIL-STD-810G Certified • 14' Drop, Altitude, -51°C to 71°C Storage Temperature, -10°C to 55°C Operating Temperature, Temperature Shock, Rain, Humidity, Sand and Dust, Vibration, Shock) • Class I Division 2 certified, Groups ABCD (optional configuration) • EU Directive RoHS 2 (2011/05/EU) • EU Directive ErP (2009/125/EC) • EU Directive WEEE (2012/19/EC) 		

For more information please visit www.MotionComputing.com or www.xplorettech.com

1-866-682-2538

* Ask your representative for more information

** Compatible with Verizon 4G LTE networks where available. Standard 4G LTE and AWS spectrums supported.

¹ Weight represents approximate system weight measured with a 40Whr battery. Actual system weight may vary depending on component and manufacturing variability.

² Battery life varies by configuration, applications in use, utilized features and operating conditions. Maximum battery capacity decreases with time and use. Motion battery life estimates based on MobileMark® 2012 performance testing.

³ Approximate charging time. Validated charging from 5% to 90% with system on or system off.

† CID2 certification is available as an optional configuration.



The Intel® Core™ vPro™ processor is designed to strengthen security across the enterprise.